

AR-S Series Compression Seal

AR-S - Architectural Applications



Movement Rating: ±50%

Product Guide



- ▶ Heavy pedestrian / light duty vehicular loading capabilities
- ▶ Appropriate for horizontal & vertical applications where watertight conditions are required.
- ▶ Comprised of a tough synthetic rubber called "Santoprene": Superior movement while being highly resistant to UV degradation, extreme temperatures, and chemicals
- ▶ Heat weldable for watertight seams & transition points
- ▶ Industry unique profile ensures against waviness or bulging while addressing high load resistance
- ▶ Unique design incorporates ribs on side faces to aid in pooling epoxy and adding surface area for increased adhesion
- ▶ Profile engineered for improved ease of installation
- ▶ Color Seals available- Contact your Rep. for more information
- ▶ Lateral shear capable to 25%± nominal joint width.

Application	System	Nominal Joint Width Install Range		H1		H2	
				Seal Height		Installed Depth	
		US	mm	US	mm	US	mm
Architectural Compression Seals	AR-100S	3/4"-1 1/4"	19-32	2"	51	2 3/16"	56
	AR-200S	1 5/8"-2 3/8"	41-60	2 3/16"	56	2 3/8"	60
	AR-300S	2 1/2"-3 3/8"	63-86	3 5/16"	84	3 1/2"	89
	AR-400S	3 1/2"-4 3/8"	89-111	3 5/16"	84	3 1/2"	89

IPC.888/REV.21

AR-S Series

Compression Seal Systems

AR - S Compression Seal
(2" (50mm) seal shown)

