



Palladium® 3D Trim

Wall System



Inside & Outside Corners



Horizontal & Vertical Boards



Product Details

- Provides a low-maintenance, permanently mounted system that coordinates with existing door and wall protection products
- Offers the durable protection of rigid sheet membrane-pressed onto MDF board, withstanding daily abuse from wheelchairs, carts, luggage and more
- Mouldings available in various thicknesses, lengths and widths to suit any application
- Horizontal boards have optional pre-cut notch for ease of installation over existing rigid sheet or other existing wall cladding

Options

- Available in Standard Inpro Solid Colours, Patterns, Woodgrains, and Metallic Finishes

Testing & Certification

- Scratch and stain resistant rigid vinyl
- UL-723 (ASTM E-84) Class A Classified
- Self-Extinguishing: Tested in accordance with the procedures specified in ASTM D-635-74
- Impact Strength: Tested in accordance with the procedures specified in ASTM D-256
- In compliance with article 15, part 1120 of the New York State uniform fire prevention and building code. DOS # 09960-930.504.4001
- ASTM G-21 and ASTM G-22 Tested does not support fungal or bacterial growth
- ASTM D-256 Impact Resistant
- Meets UL GREENGUARD Gold low-VOC emission standards. UL GREENGUARD Gold Certification ensures that products are acceptable for use in places such as schools and healthcare facilities, and that they comply with CDPH Standards.

Palladium® 3D Trim

Wall System

PART 1 – GENERAL

1.01 SUMMARY

A. Wall system for wall protection and decoration

1.02 SECTION INCLUDES

- A. Palladium Full Height Wall System
- B. Palladium Partial Height Wall System
- C. Palladium Wall System with Vertical Joints Using Colour Matched Caulk

1.03 REFERENCES

- A. American Society for Testing and Materials (ASTM)
- B. National Building Code of Canada (NBC)
- C. National Fire Protection Association (NFPA)
- D. Society of Automotive Engineers (SAE)
- E. Underwriters Laboratory (UL)
- F. Underwriters Laboratory of Canada (ULC)
- G. Uniform Building Code (UBC)

1.04 SYSTEM DESCRIPTION

A. Performance Requirements: Provide rigid vinyl sheet systems that conform to the following requirements of regulatory agencies and the quality control of IPC Door and Wall Protection Systems™, Inpro Corporation.

1. Fire Performance Characteristics: Provide UL Classified IPC Rigid Vinyl Sheet conforming with the NFPA Class A fire rating. Surface burning characteristics as determined by UL-723 (ASTM E-84), for IPC Rigid Vinyl Sheet installed with 3M Fastbond 30, Inpro Bond Adhesive, or Formulated Solutions, LLC "XT-2000+" Adhesive shall be a maximum flame spread of 20 and a maximum smoke developed of 350 for 1.5mm thick material. Provide ULC (Canada) listed IPC Rigid Vinyl Sheet conforming to the requirements of the National Building Code of Canada 2010, Subsection 3.1.13. Surface burning characteristics, as determined by CAN/ULC-S102.2, shall be flame spread of 15 and smoke developed of 30.
2. Fire Performance Characteristics: Provide Palladium 3D Boards conforming with the NFPA Class A fire rating. Surface burning characteristics as determined by ASTM E-84 shall be flame spread of 25 and smoke developed of 400.
3. Self-Extinguishing: Provide rigid vinyl sheet with a CC1 classification, as tested in accordance with the procedures specified in ASTM D-635-74, Standard Test Method for Rate of Burning and/or Extent and Time of Burning of Self-Supporting Plastics in a Horizontal Position, as referenced in UBC 52-4- 1988.
4. Provide sheet materials that have been tested and results filed in compliance with article 15, part 1120 of the New York State uniform fire prevention and building code. DOS # 09960-930.504.4001.
5. Impact Strength: Provide IPC Rigid Vinyl Sheet that has an Impact Strength of 30.4 ft-lbs/ inch of thickness as tested in accordance with the procedures specified in ASTM D-256-90b, Impact Resistance of Plastics.
6. Chemical and Stain Resistance: Provide rigid vinyl sheet that show resistance to stain when tested in accordance with applicable provisions of ASTM D-543.
7. Fungal and Bacterial Resistance: Provide rigid

vinyl that does not support fungal or bacterial growth as tested in accordance with ASTM G-21 and ASTM G-22.

8. Colour Consistency: Provide components matched in accordance with SAE J-1545 - (Delta E) with a colour difference no greater than 1.0 units using CIE Lab, CIE CMC, CIE LCh, Hunter Lab or similar colour space scale systems.

1.05 SUBMITTALS

- A. Product Data: Manufacturer's printed product data for each type of IPC Rigid Vinyl Sheet specified.
- B. Detail Drawings: Mounting details with the appropriate adhesives for specific project substrates.
- C. Samples: Verification samples of IPC Rigid Vinyl Sheet, 203mm square of each type and colour indicated.
- D. Manufacturer's Installation Instruction: Printed installation instructions for IPC Rigid Vinyl Sheet.

1.06 DELIVERY, STORAGE AND HANDLING

- A. Deliver materials in unopened factory packaging to the jobsite.
- B. Inspect materials at delivery to assure that specified products have been received.
- C. Store in original packaging in a climate-controlled location away from direct sunlight.

1.07 PROJECT CONDITIONS

A. Environmental Requirements: Products must be installed in an interior climate-controlled environment.

1.08 WARRANTY

A. Standard IPC Limited Lifetime Warranty against material and manufacturing defects.

PART 2 – PRODUCTS

2.01 SUPPLIER

A. Acculine Architectural Systems: 135-139 Northcorp Blvd, Broadmeadows VIC 3047, Telephone: (03) 9334 5911, www.acculine.com.au

2.02 MANUFACTURER

A. Basis-Of-Design Product: Inpro Corporation, IPC Door and Wall Protection Systems PO Box 406 Muskego, WI 53150 USA; Telephone: 800.222.5556, Fax: 888.715.8407, Website: www.inprocorp.com.

1. Submit comparable products of one the following for approval by architect:

- a. Insert name of manufacture of comparable product
- b. Submit requests for substitution in accordance with Instructions to Bidders and Division 01 General Requirements
- c. Provide specified product; Owner will not consider substitution requests.

2.03 MANUFACTURED UNITS

Note to Specifier – Update Section Below as Needed and Delete

A. Rigid Sheet

1. IPC Rigid Sheet Options (Dimensions; Thickness – Item Number)

- a. 0.91m x 2.44m; 1mm, available - 305
- b. 0.91m x 2.44m; 1.5mm, available - 306
- c. 1.22m x 2.44m; 1mm, standard - 405
- d. 1.22m x 2.44m; 1.5mm, standard - 406
- e. 1.22m x 2.44m; 2mm, available - 410

2. 3048mm sheets, 24m rolls, 37m rolls and custom sizes available.

3. Backing – unbacked

B. Mouldings

1. Palladium 3D Boards (Description, Thickness, Width, Length)

- a. Horizontal Board: 13mm thick, 51mm, 76mm, 102mm, 152mm or 203mm wide, 2.44m long.
- b. Horizontal Top Cap Board: 13mm thick, 51mm, 76mm, 102mm, 152mm or 203mm wide, 2.44m long.
- c. Vertical Boards: 10mm thick, 51mm, 76mm, 102mm, 152mm or 203mm wide, 2.44m long.
- d. Inside Corners Partial Height: 10mm thick, 51mm, 76mm, 102mm, 152mm or 203mm wide, 2.44m long, 90° and 135°.
- e. Inside Corners Full Height: 16mm thick, 51mm, 76mm, 102mm, 152mm or 203mm wide, 2.44m long, 90° and 135°.
- f. Outside Corners Partial Height: 10mm thick, 51mm, 76mm, 102mm, 152mm or 203mm wide, 2.44m long, 90° and 135°.
- g. Outside Corners Full Height: 16mm thick, 51mm, 76mm, 102mm, 152mm or 203mm wide, 2.44m long, 90° and 135°.
- h. Trim Cap#2, 13mm thick x 51mm wide, 2.44m long

2.04 MATERIALS

A. Vinyl: IPC Rigid Sheet shall be manufactured from chemical and stain resistant unplasticized polyvinyl chloride (uPVC) with the addition of impact modifiers. No plasticizers shall be added (plasticizers may aid in bacterial growth). Accent strips when used shall be of polyvinyl chloride (PVC).

2.05 MOULDING

A. Palladium 3d Boards: 3D boards shall be made from 1mm IPC Rigid Sheet factory bonded to MDF Board. MDF board shall have No Added Urea Formaldehyde.

2.06 FINISHES

- A. Colour or pattern of IPC Sheet to be selected by the architect from the IPC Sheet finish selection. Surface shall have a velvet texture.
- B. Colour or pattern of Palladium 3D Wall Boards to be selected by the architect from the IPC finish selection. Surface shall have a velvet texture. Back of 3D moulding shall be black melamine.

PART 3 – EXECUTION

3.01 EXAMINATION

- A. Examine areas and conditions in which the Palladium 3D Wall System will be installed.
 1. Complete all finishing operations, including painting, before beginning installation of rigid vinyl sheet materials.
- B. Wall surface shall be dry and free from dirt, grease and loose paint.

3.02 PREPARATION

- A. Surface Prep: Prior to installation, clean the substrate to remove dust, debris and loose particles. Ensure the substrate is sound and per project plans.
- B. Acclimate product in temperatures between 18°-27°C and a humidity level less than 80% 24 hours in advance of installation.



Palladium® 3D Trim

Wall System

C. The area of installation must temperature and humidity controlled for at least 48 hours after installation.

3.03 INSTALLATION

A. General: Locate the Palladium 3D Wall System as indicated on the approved detail drawing for the appropriate substrate and in compliance with the IPC installation instructions. Install level and plumb at the height indicated on the drawings.

3.04 CLEANING

A. At completion of the installation, clean surfaces in accordance with the IPC clean-up and maintenance instructions